

BẢNG LIỆT KÊ CÁC DÒNG SẢN PHẨM CYBEROAM

	SOHO						SMB				Large Ens
	CR15wiNG	CR25wiNG	CR35wiNG	CR15iNG	CR25iNG	CR35iNG	CR50iNG	CR100iNG	CR200iNG	CR300iNG	CR2500iNG
Hardware Specifications											
Copper GbE Ports	3	4	6	3	4	6	8	8	10	10	14
1GbE SFP (Mini GBIC) Ports	-	-	-	-	-	-	-	-	-	-	4
10GbE SFP (Mini GBIC) Ports	-	-	-	-	-	-	-	-	-	-	2
Console Ports (RJ45)	1	1	1	1	1	1	1	1	1	1	1
USB Ports	2	2	2	2	2	2	2	2	2	2	2
Hardware Bypass Segments [#]	-	-	-	-	-	-	2	2	2	2	2
Configurable Internal/DMZ/WAN Ports	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
System Performance*											
Firewall Throughput (UDP) (Mbps)	1.000	1.500	2.300	1.000	1.500	2.300	3.250	4.500	10.000	12.000	40.000
Firewall Throughput (TCP) (Mbps)	750	1.000	2.000	750	1.000	2.000	3.000	3.500	8.000	9.500	28.000
New sessions/second	3.500	5.000	12.000	3.500	5.000	12.000	30.000	45.000	70.000	85.000	200.000
Concurrent sessions	60.000	150.000	350.000	60.000	150.000	350.000	1.000.000	1.250.000	1.500.000	2.000.000	3.500.000
IPSec VPN Throughput (Mbps)	110	210	250	110	210	250	400	450	800	1.200	8.000
No. of IPSec Tunnels	50	100	150	50	100	150	200	250	300	400	3.000
SSL VPN Throughput (Mbps)	50	75	100	50	75	100	300	400	450	500	1.000
WAF Protected Throughput (Mbps)	-NA-	45	65	-NA-	45	65	300	500	650	850	1.000
Anti-Virus Throughput (Mbps)	180	300	525	180	300	525	1.000	1.400	2.200	2.600	6.000
IPS Throughput (Mbps)	140	200	350	140	200	350	750	1.200	2.000	2.400	6.000
UTM Throughput (Mbps)	80	110	210	80	110	210	550	750	1.200	1.500	4.500
Authenticated Users/Nodes	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited

If Enabled, will bypass traffic only in case of Power failure.

* Antivirus, IPS and UTM performance is measured based on HTTP traffic as per RFC 3511 guidelines. Actual performance may vary depending on the real network traffic environments.